

2.23m²/box 48 box/pallet
122 x 610 x (4/0.5mm)(1mm Underlay built in)

Product

Click LVT Rigid Core SPC	EN ISO 10582	SPC Flooring
Installation		Unilin Angle
Application	EN ISO 10874	22/33

Specification

Thickness	EN ISO 24337	4.0mm & 1mm underlay built on
Weight	EN ISO 24342	2.08kg/m ³
Wear Layer	EN ISO 24346	0.5mm

Product Properties

Property	Test Method	Result
Indoor Air Certificate		Floor-score
Fire Resistance	EN 13501-1	BFI-S1
Residual Indentation	EN ISO 24343-1(2.5h)	<0.1mm
Dimensional Stability	EN ISO 23999(80°C/6h)	<0.1%
Colour Fastness	EN ISO 105-B02	≥6
Slip Resistance	EN 13893	DS (>0.3)
Electrical Propensity	EN1815	<2kv
Wear and Scratch Resistance	EN 16094	Pass with good result
Chemical Resistance	EN ISO 26987	Pass with good result
Effect of Castor Chair	EN 425	Suitable
Underfloor Heating		Ok (max +27°C)
Anti Bacterial Growth		Does not act as substrate

Wood Innovations 9 Springhill Road, Newry, County Down, N. Ireland. BT35 6EF

Tel: 028 4177 3366

Email: sales@woodinnovations.co.uk

www.woodinnovations.com